



XCOMP

PERFORMANCE TIRES

LIGHT TRUCK PERFORMANCE TIRE CATALOG

2025

NEVER COMPROMISE[®]



EXPERIENCE THE DIFFERENCE



***X COMP® PERFORMANCE TIRES
DELIVER THE RELIABILITY FOR
DAILY DRIVING. THE SUPERIOR
ENGINEERING AND DURABLE
CONSTRUCTION ON OUR OFF-
ROAD TIRES ALSO GIVES
THE VERSATILITY TO BE DRIVEN
AGGRESSIVELY ON ANY
TERRAIN. NEVER COMPROMISE!***

**RACE
PROVEN
TIRES**







XCOMP M/T

AGGRESSIVE IS AN UNDERSTATEMENT, THIS TIRE IS A BEAST! MAXIMUM TRACTION AND GRIP ON THE SHOULDER AREA OF THE TIRE, WHEN IT'S NEEDED MOST!

HIGH PERFORMANCE COMPOUND

FEATURES IMPROVED WET AND DRY TRACTION AS WELL AS EXCELLENT WEAR AND TEAR RESISTANCE, ESPECIALLY IN HARSH OFF-ROAD CONDITIONS.

TREAD BLOCK CORNERS

CONTOURED CORNERS OF THE INNER RIB BLOCKS GIVE INCREASED DRIVING STABILITY IN CONTROL ON UNPAVED ROAD CONDITIONS. RIB BLOCK DESIGNED FOR EFFECTIVE SELF-CLEANING.

SHOULDER STABILITY AND SIDEWALL DESIGN

AGGRESSIVE TREAD AND SIDEWALL DESIGN ENHANCES TRACTION IN ALL OFF-ROAD CONDITIONS. REINFORCED SHOULDER GROOVES ADD ADDITIONAL PERFORMANCE WITHOUT COMPROMISING TREAD BLOCK STIFFNESS.



XCOMP M/T



M/T FEATURES AND SIDEWALL DESIGN

- AGGRESSIVE IS AN UNDERSTATEMENT, THIS TIRE IS TRULY A BEAST!
- MAXIMUM GRIP ON THE SHOULDER AREA OF THE TIRE WHEN IT'S NEEDED MOST!
- OFFERS SUPERIOR OFF-ROAD PERFORMANCE WHILE DELIVERING A SMOOTH, QUIET RIDE.
- COVERED BY U.S. PATENT#: D808.895 S
- 100% FREE REPLACEMENT WARRANTY
- 30 DAY SATISFACTION WARRANTY
- FREE ROAD HAZARD PROTECTION
- M&S RATED







XCOMP M/T SIZES AND SPECS

TIRE SIZE	LOAD INDEX (S/D)	SPEED SYMBOL	PLY	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	LOAD CAPACITY (S/D) LBS
31X10.50R15LT	109	Q	6	30.5	10.6	19	2270
35X12.50R15LT	118	Q	8	34.5	12.5	19	2910
LT265/75R16	123/120	Q	10	31.7	10.5	19	3415/3085
LT285/75R16	126/123	Q	10	32.8	11.3	19	3750/3415
33X12.50R17LT	126	Q	10	32.5	12.5	20	3750
35X12.50R17LT	126	Q	10	34.5	12.5	20	3750
37X13.50R17LT	131	Q	10	36.5	13.6	20	4300
40X13.50R17LT	131	Q	10	39.5	13.6	20	4300
42X14.50R17LT	121	Q	6	41.5	14.4	20	3195
LT265/70R17	123/120	Q	10	31.7	10.7	19	3195/2910
LT285/70R17	121/118	Q	10	32.8	11.5	19	3195/2910
LT285/75R17	121/118	P	10	33.9	11.3	19	3195/2910
LT295/70R17	128/125	P	12	33.3	11.8	19	3970/3640
LT315/70R17	121/118	P	12	34.4	12.7	19	3195/2910
33X12.50R18LT	121	Q	12	32.5	12.5	20	2910
35X12.50R18LT	128	Q	12	34.5	12.5	20	3970
LT275/70R18	125/122	P	10	33.2	11.0	19	3640/3305
LT285/65R18	125/122	Q	10	32.6	11.5	19	3640/3305
33X12.50R20LT	114	Q	12	32.5	12.5	20	2600
35X12.50R20LT	125	Q	12	34.5	12.5	20	3640
37X13.50R20LT	128	Q	12	36.5	13.6	20	3970
40X13.50R20LT	128	Q	10	39.5	13.6	20	3970
LT295/55R20	123/120	P	10	32.8	12.2	19	3415/3085
LT295/60R20	126/123	P	10	33.9	11.8	19	3750/3415
LT295/65R20	129/126	P	10	35.1	11.8	19	4080/3750
LT305/55R20	125/122	Q	12	33.2	12.4	19	3640/3305
33X12.50R22LT	114	Q	12	32.5	12.5	20	2600
35X12.50R22LT	121	Q	12	34.5	12.5	20	3195
37X13.50R22LT	128	Q	12	36.5	13.6	20	3970
35X12.50R24LT	117	Q	10	34.5	12.5	20	2835
37X13.50R24LT	124	Q	12	36.5	13.6	20	3525
37X13.50R26LT	117	Q	10	36.5	13.6	20	2835

All X COMP M/T'S COVERED BY U.S. PATENT NO: D808,895 S



XCOMPTIRES.COM



800.944.8414



@XCOMP_TIRES



XCOMP X/T

THE ULTIMATE CROSSOVER BETWEEN AN M/T AND A/T, THE X/T WILL DELIVER SUPERIOR DAILY DRIVING PERFORMANCE WHILE MAINTAINING THE AGGRESSIVE AESTHETIC FOR ANY LIGHT TRUCK.

HIGH PERFORMANCE COMPOUND

FEATURES IMPROVED WET AND DRY TRACTION AS WELL AS EXCELLENT WEAR AND TEAR RESISTANCE, ESPECIALLY IN HARSH OFF-ROAD CONDITIONS.

CUTTING EDGE TREAD DESIGN

SHOULDER TREAD BLOCKS DESIGNED SPECIFICALLY FOR NOISE REDUCTION WHILE MAINTAINING SUPERIOR OFF-ROAD PERFORMANCE AND DAILY DRIVING SUPPORT.

PATENTED SIDEWALL DESIGN

AGGRESSIVE SIDEWALL FOR ENHANCED PROTECTION AND TRACTION. REINFORCED SHOULDER GROOVES ADD ADDITIONAL PERFORMANCE WITHOUT COMPROMISING TREAD BLOCK STIFFNESS.



XCOMP X/T



*50,000 MILEAGE WARRANTY FOR P METRIC SIZES

X/T FEATURES AND SIDEWALL DESIGN

- THE ULTIMATE CROSSOVER BETWEEN THE M/T AND A/T.
- THE X/T WILL DELIVER SUPERIOR DAILY DRIVING PERFORMANCE WHILE MAINTAINING THE AGGRESSIVE AESTHETIC FOR ANY LIGHT TRUCK.
- SHOULDER TREAD BLOCKS DESIGNED FOR NOISE REDUCTION AND AN AGGRESSIVE SIDEWALL FOR ENHANCED PROTECTION AND TRACTION.
- COVERED BY U.S. PATENT#: D973,576 S
- 100% FREE REPLACEMENT, 30 DAY SATISFACTION WARRANTY
- FREE ROAD HAZARD PROTECTION
- 45,000 MILE WARRANTY (50,000 ON P METRIC SIZES)
- 3 PEAK SNOW RATED!







XCOMP X/T SIZES AND SPECS

TIRE SIZE	LOAD INDEX (S/D)	SPEED SYMBOL	PLY	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	LOAD CAPACITY (S/D) LBS
LT265/75R16	123/120	Q	10	31.7	10.5	16	3415/3085
33X12.50R17LT	126	Q	10	32.5	12.5	18	3750
35X12.50R17LT	126	Q	10	34.5	12.5	18	3750
37X12.50R17LT	124	Q	8	36.5	12.5	18	3525
40X13.50R17LT	131	Q	10	39.5	13.6	18	4300
LT285/70R17	121/118	Q	10	32.8	11.5	16	3195/2910
LT295/70R17	121/118	Q	10	33.3	11.8	16	3195/2910
33X12.50R18LT	122	Q	12	32.5	12.5	18	3305
35X12.50R18LT	128	Q	12	34.5	12.5	18	3970
LT275/70R18	125/122	Q	10	33.2	11.0	16	3640/3305
LT295/70R18	129/126	Q	10	34.3	11.8	16	4080/3750
33X11.50R20LT	118	Q	10	32.5	11.4	18	2910
33X12.50R20LT	119	Q	12	32.5	12.5	18	3000
35X12.50R20LT	125	Q	12	34.5	12.5	18	3640
37X13.50R20LT	128	Q	12	36.5	13.6	18	3970
40X13.50R20LT	128	Q	10	39.5	13.6	18	3970
LT275/65R20	126/123	Q	10	34.1	11.0	16	3750/3415
LT285/55R20	122/119	Q	10	32.4	11.7	16	3305/3000
LT285/60R20	125/122	Q	10	33.5	11.5	16	3640/3305
LT295/55R20	123/120	Q	10	33.8	12.2	16	3415/3085
LT305/55R20	125/122	Q	12	33.2	12.4	16	3640/3305
33X12.50R22LT	114	Q	12	32.5	12.5	18	2600
35X12.50R22LT	121	Q	12	34.5	12.5	18	3195
35X12.50R24LT	117	Q	10	34.5	12.5	18	2835
37X13.50R24LT	124	Q	12	36.5	13.6	18	3525

All X COMP X/T'S COVERED BY U.S. PATENT NO: D973,576 S



XCOMPTIRES.COM



800.944.8414



@XCOMP_TIRES



XCOMP A/T

THE A/T TREAD AREA IS AN AGGRESSIVE DESIGN, YET SUITABLE FOR EVERYDAY DRIVING, CONDITIONS WITH ALL-SEASON AND 3 PEAK SNOWFLAKE RATINGS!

HIGH PERFORMANCE COMPOUND

SNOW FLAKE QUALIFIED TREAD FEATURES ENHANCED SIPING AND AN ADVANCED COMPOUND THAT OFFERS EXCELLENT WET AND DRY TRACTION, AS WELL AS CERTIFIED TRACTION IMPROVEMENTS ON SNOW AND ICE.

ANGLED GROOVES AND Z-SHAPED SIPES

ANGLED LATERAL AND LONGITUDINAL GROOVE STRUCTURE PROMOTES BETTER DRAINAGE FOR IMPROVED BRAKING AND HANDLING ON WET, SOGGY SURFACES. THE DEEP TWO-STEP SLOTS ON SHOULDER BLOCKS HAVE THE SAME SERVICE LIFE AS THE TREAD.

PUNCTURE RESISTANT SHOULDERS

THE FULLY-WRAPPED SHOULDER HAS A ROUGH VISUAL SENSE AND FUNCTIONALITY PREVENT SHARP CUTS, SCRATCHES, AND IMPACT DAMAGE. IN ADDITION, IT PROVIDES ADDITIONAL TRACTION IN MUDDY AND SNOWY CONDITIONS.



XCOMP A/T



*60,000 MILEAGE WARRANTY FOR P METRIC SIZES

A/T FEATURES AND SIDEWALL DESIGN

- THE X COMP A/T DELIVERS THE RELIABILITY AND HIGH PERFORMANCE FOR DAILY DRIVING.
- THE SUPERIOR ENGINEERING AND DURABLE CONSTRUCTION ALSO GIVES THE A/T THE VERSATILITY TO BE DRIVEN AGGRESSIVELY ON ANY TERRAIN.
- THE TIRE CASING HAS TWO FULL PLYS OF POLYESTER WITH FULL SIDEWALL TURN UP, TO ENABLE A MORE COMFORTABLE RIDE, YET VERY STRONG AND DURABLE.
- THE TREAD AREA IS AN AGGRESSIVE DESIGN, YET SUITABLE FOR EVERYDAY DRIVING CONDITIONS.
- THE A/T IS VERY QUIET WITH A SMOOTH CONTROLLED RIDE, BOTH ON AND OFF ROAD.
- 100% FREE REPLACEMENT, 30 DAY SATISFACTION WARRANTY
- FREE ROAD HAZARD PROTECTION
- 50,000 MILE WARRANTY (55,000 FOR P METRIC SIZES)
- 3 PEAK SNOW RATED!





A/T | 37X13.50R17LT

XCOMP
PERFORMANCE TIRES

**RACE
PROVEN
TIRES**



XCOMP A/T SIZES AND SPECS

TIRE SIZE	LOAD INDEX (S/D)	SPEED SYMBOL	PLY	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	LOAD CAPACITY (S/D) LBS
LT245/75R16	120/116	S	10	30.5	9.8	15	3085/2755
LT265/75R16	123/120	R	10	31.7	10.5	15	3415/3085
LT285/75R16	126/123	Q	10	32.8	11.3	16	3750/3415
33X12.50R17LT	126	Q	10	32.5	12.5	16	3750
35X12.50R17LT	126	Q	10	34.5	12.5	16	3750
37X13.50R17LT	131	Q	10	36.5	13.6	16	4300
40X13.50R17LT	131	Q	10	39.5	13.6	16	4300
LT235/80R17	120/117	R	10	31.8	9.3	15	3042/2835
LT245/75R17	121/118	S	10	31.5	9.8	15	3195/2910
LT285/75R17	128/125	S	10	33.9	11.3	16	3970/3640
LT315/70R17	121/118	S	10	34.4	12.7	16	3195/2910
P265/70R17	113	S	-	31.7	10.7	13	2535
LT265/70R17	123/120	S	10	31.7	10.7	16	3195/2910
LT285/70R17	126/123	Q	10	32.8	11.5	16	3195/2910
33X12.50R18LT	118	Q	10	32.5	12.5	16	2910
35X12.50R18LT	123	T	10	34.5	12.5	16	3415
LT265/70R18	124/121	Q	10	32.6	10.7	16	3525/3195
LT275/65R18	123/120	Q	10	32.1	11.0	16	3415/3085
LT275/70R18	125/122	S	10	33.2	11.0	16	3640/3305
LT285/65R18	125/122	S	10	32.6	11.5	16	3640/3305
LT295/70R18	129/126	S	10	34.3	11.8	16	4080/3750
33X12.50R20LT	114	Q	10	32.5	12.5	16	2600
35X12.50R20LT	121	T	10	34.5	12.5	16	3195
37X12.50R20LT	126	Q	10	36.5	12.5	16	3750
37X13.50R20LT	127	Q	10	36.5	13.6	16	3860
40X13.50R20LT	128	Q	10	39.5	13.6	16	3970
LT265/60R20	121/118	S	10	32.5	10.7	16	3195/2910
P275/55R20XL	117	T	-	31.9	11.2	13	2835
LT275/55R20	120/117	S	10	31.9	11.2	16	3085/2835
LT275/65R20	126/123	S	10	34.1	11.0	15	3750/3415
LT285/55R20	122/119	Q	10	32.4	11.7	16	3305/3000
LT285/65R20	127/124	Q	10	34.6	11.5	16	3860/3525
LT295/65R20	129/126	S	10	35.1	11.8	16	4080/3750
LT305/55R20	125/122	Q	12	33.2	12.4	16	3640/3305
LT325/60R20	126/123	R	10	35.4	13	16	3750/3415
P285/45R22XL	114	H	-	32.1	11.2	13	2601



XCOMP H/T ASII SIZES AND SPECS

TIRE SIZE	LOAD INDEX (S/D)	SPEED SYMBOL	PLY	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	LOAD CAPACITY (S/D) LBS
235/75R15 XL	109	T	-	28.86	9.25	11	2271
215/70R16	100	H	-	27.87	8.7	11	1764
225/70R16	103	H	-	28.43	8.98	11	1929
235/70R16	106	T	-	28.98	9.45	11	2094
245/70R16	107	T	-	29.53	9.76	11	2149
245/75R16	111	T	-	30.47	9.76	11	2403
255/70R16	111	T	-	30.08	10.24	11	2403
265/70R16	112	T	-	30.63	10.71	11	2469
265/75R16	116	T	-	31.65	10.51	11	2756
215/60R17	96	H	-	27.17	8.7	11	1565
225/65R17	102	T	-	28.5	8.98	11	1874
235/65R17	104	H	-	29.06	9.45	11	1984
245/65R17	107	H	-	29.53	9.76	11	2149
245/70R17	110	T	-	30.55	9.76	11	2337
255/65R17	110	T	-	30.08	10.24	11	2337
255/70R17	112	T	-	31.1	10.24	11	2469
265/65R17	112	T	-	30.55	10.71	11	2469
265/70R17	115	T	-	31.65	10.71	11	2679
225/55R18	98	V	-	27.76	9.17	11	1653
225/60R18	100	V	-	28.62	8.98	11	1764
235/55R18	100	V	-	28.15	9.65	11	1764
235/60R18	103	H	-	29.09	9.45	11	1929
235/65R18	106	H	-	30.04	9.45	11	2094
245/60R18	105	H	-	29.57	9.76	11	2039
255/65R18	111	H	-	31.06	10.24	11	2403
255/70R18	113	T	-	32.09	10.24	11	2535
265/60R18	110	H	-	30.51	10.71	11	2337
265/65R18	114	T	-	31.54	10.71	11	2601

TIRE SIZE	LOAD INDEX (S/D)	SPEED SYMBOL	PLY	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	LOAD CAPACITY (S/D) LBS
265/70R18	116	H	-	32.64	10.71	11	2756
275/65R18	116	H	-	32.09	10.98	11	2756
225/55R19	99	V	-	28.78	9.17	11	1709
235/45R19 XL	99	V	-	27.36	9.29	11	1709
235/50R19	99	V	-	28.31	9.65	11	1709
235/55R19 XL	105	V	-	29.17	9.65	11	2039
245/55R19	103	V	-	29.65	9.96	11	1929
255/60R19	109	H	-	31.06	10.24	11	2271
235/55R20	102	V	-	30.16	9.65	11	1874
245/50R20	102	V	-	29.69	9.96	11	1874
255/50R20 XL	109	V	-	30.08	10.43	11	2271
255/55R20 XL	110	V	-	31.02	10.43	11	2337
265/50R20	107	V	-	30.47	10.91	11	2149
275/50R20	109	H	-	30.87	11.18	11	2271
275/55R20 XL	117	T	-	31.89	11.18	11	2833
275/60R20	115	T	-	32.99	10.98	11	2679
285/45R22 XL	114	H	-	32.09	11.22	11	2601
LT215/85R16	115/112	S	10	30.39	8.5	14	2680/2470
LT225/75R16	115/112	S	10	29.29	8.78	14	2680/2470
LT235/85R16	120/117	S	10	31.73	9.25	14	3085/2755
LT245/75R16	120/117	S	10	30.47	9.76	14	3085/2755
LT265/75R16	123/120	S	10	31.65	10.51	14	3415/3085
LT235/80R17	120/117	S	10	31.81	9.25	14	3085/2835
LT245/70R17	119/116	S	10	30.55	9.76	14	3000/2755
LT245/75R17	121/118	S	10	31.5	9.76	14	3195/2910
LT265/70R17	123/120	S	10	31.65	10.71	14	3415/3085
LT275/65R18	123/120	S	10	32.09	10.98	14	3415/3085
LT275/70R18	125/122	S	10	33.19	10.98	14	3640/3305
LT275/65R20	126/123	S	10	32.09	10.98	14	3750/3415

XCOMP H/T ASII

**NEW
PRODUCT**

LIGHT TRUCK AND SUV OWNERS CAN NOW HIT THE HIGHWAY WITH CONFIDENCE DURING ALL WEATHER CONDITIONS. THE H/T ASII HAS THE PERFORMANCE AND LONGEVITY TO GET YOU WHERE YOU ARE HEADED SAFELY. THE SUPERB BLEND OF A QUIET RIDE, LONG TREAD LIFE, AND ALL-SEASON PERFORMANCE IS UNMATCHED.

HIGH PERFORMANCE DESIGN

DESIGNED TO ENHANCE PERFORMANCE FOR A WIDE RANGE OF CUV, SUV, AND LIGHT TRUCKS. LONG TREAD LIKE COMBINED WITH BALANCED ON-ROAD PERFORMANCE.

DEEP SIPING/GROOVES

FULL-DEPTH SIPING FOR EXCEPTIONAL ALL-WEATHER TRACTION AND WIDE CIRCUMFERENTIAL GROOVES ALLOWS RAPID WATER EVACUATION PROVIDING EXCELLENT HYDROPLANING RESISTANCE.

LARGE TREAD BLOCKS

LARGE TREAD BLOCKS INCREASES THE CONTACT AREA, IMPROVING OVERALL HANDLING AND TREADWEAR.



*60,000 MILEAGE WARRANTY FOR P METRIC SIZES

100% FREE REPLACEMENT WARRANTY

American Pacific Industries, Inc (API) hereby warrants every new Gladiator Light Truck (X Comp) tire for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out. API will refund the cost of a replacement Gladiator X Comp tire. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner. All Exclusions listed below void this 100% Free Replacement Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) The Gladiator X Comp tire must be replaced with a comparable new Gladiator X Comp tire by an authorized Gladiator dealer. Copy of invoice will be required.
- B) 100% free replacement applies to new first quality tires. Blemished tires, retreads and road hazard tires are specifically excluded (see Road Hazard Warranty below),
- C) Adjustments on ride complaints or out of round tires are excluded from this warranty if they are worn past 2/32" from the original usable tread of the new tire.

FREE ROAD HAZARD WARRANTY

Every applicable Gladiator X Comp tire that has been irreparably damaged due to a normal road hazard condition (e.g. irreparable cut, puncture, snag, bruise, or impact break) within the first 25% of the original tread depth and within 2 years from the date of purchase will be replaced free of charge with an equivalent Gladiator X Comp tire. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner. To be eligible, you must present your original invoice showing date of purchase. All Exclusions listed below void this Road Hazard Warranty. Conditions and coverage are subject to change at any time and without notice. ALL ROAD HAZARD CLAIMS MUST BE SERVICED THROUGH YOUR AUTHORIZED GLADIATOR X COMP DEALER. Applicable X Comp Lines with Road Hazard Warranty: X Comp M/T, X Comp X/T and X Comp A/T, X Comp H/T ASII, X Comp H/P AS1

SATISFACTION ASSURED

All API passenger and X Comp tires are covered by the 30 Day "Satisfaction Assured" trial period. If, for any reason, other than an excluded condition listed in the respective tire's Standard Warranty, you are not satisfied with your new set of tires within 30 days of date of purchase - or the first 2/32nds of tread wear as measured in the fastest wearing groove (whichever comes first) - you may exchange all or any one of them for the same number of the same design or similar design API manufactured tires. Mounting and balancing are free of charge (excluding online orders). Owner pays all applicable taxes. If you wish to exchange for another set of API manufactured tires that have a higher cost, you must pay the upgrade from the original purchase price, including shipping and all applicable taxes. If you wish to exchange for another set of tires, which is at a lower cost, you will receive a credit for the difference in cost.

This Satisfaction Assurance guarantee only applies to the original new set of manufactured passenger and X Comp tires purchased and not to the replacement tires under this guarantee.

Administration of the Assured Satisfaction Warranty

Within the 30 days from the date of purchase or the first 2/32nds tread wear as measured in the fastest wearing groove, you must return your tires to the authorized API brand tire dealer where you purchased your tires. You must present the original sales receipt and proof-of-purchase. Reason for dissatisfaction must be explained to the dealer (i.e., appearance, ride, handling, etc.) and noted on the adjustment claim form.

EXCLUSIONS

- A) All Gladiator warranties are limited to the original purchaser and the original vehicle on which they are mounted, and are not assignable to subsequent purchasers or vehicles.
- B) The warranties listed above are applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by these warranties.
- C) The following is not covered by the warranties listed above:
 - 1) Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - 2) Failure, damage or irregular wear due to:
 - a) fire, accident or vandalism;
 - b) mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - c) misapplication of tire; or
 - d) alteration of the tire, addition of foreign material, transfers from one vehicle to another or any previous damages and/or repairs.
 - 3) Cost of mounting and balance service.
 - 4) Loss of time or use, inconvenience, or any incidental or consequential damages except as prohibited by law.
 - 5) Adjustment on out-of-balance or out-of-round tire is allowed only during the first 2/32" of the original tread as measured in the fastest wearing groove. A set of all four (4) tires from the same vehicle claimed for out-of-round will not be accepted.
- D) Any Gladiator X Comp tire produced five (5) years from date of manufacture as determined by the DOT/Serial number are not covered under the warranties listed above.

REPAIRS AND RETREADING: RATING CHANGES AND CAUTIONS

- A) Repaired, retreaded or altered Gladiator tire with "Speed Rating(s)" no longer retain their "Speed Rating".
- B) If the aforementioned tire(s) is repairable, see the recommended repair procedures used by the tire dealer(s) for repairing tubeless passenger car radial tires as detailed and illustrated in the RMA puncture repair procedures.
- C) Repairs must be restricted to the tread area inside a half inch of the sidewall of the tire.
- D) Do not repair any punctures that are larger than 1/4" in diameter.

OWNER'S OBLIGATIONS

In order to be eligible for Gladiator X Comp Limited Warranty service, the dealer/owner must:

- A) At the time of purchase, the tires must be properly installed, correct air pressure set and the wheels balanced. Every 6,000 miles the tires must be rotated, proper air pressures set and the wheel alignment checked.
- B) Any tire to be adjusted must be presented to an authorized Gladiator dealer.
- C) Present proof of purchase to the satisfaction of the dealer.
- D) Complete and sign a Gladiator Warranty Claim Form which is available at any authorized dealer.
- E) Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Gladiator Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein. This warranty only applies the 48 contiguous continental United States, Alaska, Hawaii, District of Columbia and Canada.